

Landscapers RS 60 – 80 – 100 N



Specifications	RS 60 N	RS 80 N	RS 100 N
Working width	60 cm	80 cm	100 cm
Weight	190 kg	260 kg	310 kg
Seed container content approx.	54 l	70 l	90 l
HONDA engine GX 160	4 kW / 5.5 HP 4 kW / 5.5 HP 4 kW / 5.5 HP		
4-stroke gas engine with automatic oil guard shut-off			
Approx. area capacity per hour	1900 m ²	2600 m ²	3200 m ²
Length/width/height approx. (with guide beam)	1750/800/ 950 mm	1750/1000/ 950 mm	1750/1200/ 950 mm
Reverse gear unit with forward and reverse gear	●	●	●
Divided pressure roller (differential drive) with maintenance-free differential gear for very easy steering and turning	○	●	●

Features

- Maintenance-free bearing points
- Wind-protected seed delivery
- Height-adjustable guide beam
- Heavy-duty tool box with tools
- Dead man's switch (safety lever)
- Two individually foldable, resilient scrapers on the pre-roller and pressure roller
- Powered seed dibbler with cleaning cage and quick depth adjustment
- Turn off device with a large on-board seed receptacle

Four Jobs in one Process

SEMBDNER landscapers allow perfect lawn seeding through the well proven seed concept which we developed in conjunction with our customers. The convenient compact construction and the already renowned durability of our products are the reason for the great national and international success of SEMBDNER landscapers.

• Pre-rolling

The pre-roller crushes the coarser clumps to prevent the seeds from sinking too deeply and being covered by too much soil.

• Planting

The sowing occurs through a flexible nylon brush, which is insensitive to impurities. Using a scale with a shut-off device, the adjustment is precise to the gram.

• Covering

Due to its cleaning cage, the powered seed dibbler also operates on rocky, clumpy or moist ground without any problems and much more evenly than stripe-producing rakes or harrows.

• Rolling

The pressure roller presses the ground surface and the seeds completely evenly, allowing the seeds to germinate much quicker.

Landscaper RS 50 H

Hand-guided



Specifications	RS 50 H
Working width	50 cm
Weight approx.	from 60 – 120 kg
Seed container-approx. content	40 l
Approx. length/width/height (with guide beam)	1270/590/940 mm

Features

- Lattice pre-roller and smooth pressure roller
- Two removable weight boxes
- Maintenance-free bearings
- Wind-protected seed delivery
- height-adjustable guide beam
- powered seed dibbler
- seed volume adjustment
- easy to transport

Scarifier VR 60 B and VR 45 A

with front wheel drive



VR 45 H

without a wheel drive

Specifications	VR 60 B	VR 45 A	VR 45 H
Front wheel drive	●	●	○
Reduction gear 55 :1 (for front wheel drive)	●	●	○
Working width	60 cm	45 cm	45 cm
Ground working depth	up to 2.5 cm	up to 2.5 cm	up to 2.5 cm
Weight	110 kg	90 kg	85 kg
HONDA engines	6.6 kW/9 HP	4 kW/5.5 HP	4 kW/5.5 HP
4-stroke gas engine with automatic oil guard shut-off			
Approx. area capacity per hour	2.000 m ²	1.500 m ²	1.500 m ²
Length/width/height approx. (with guide beam)	1360/800/ 990 mm	1360/650/ 990 mm	1360/650/ 990 mm
Steel panel housing	4 mm	4 mm	4 mm
Inflatable tires	260 x 85	260 x 85	260 x 85

Features

- Front wheel drive (VR 60 B and VR 45 A) for an even and optimum result and easy, comfortable operation, even in hilly terrain.
- Heavy-duty steel construction for continuous professional use.
- Large and wide inflatable tires as well as individually supported rear wheels for turning in the tightest space.
- Dead man's switch for simultaneous shut-off of wheel drive (VR 60 B and VR 45 A) and cutter spindle.
- Practical safety covers and ejection safeguards with movable rubber shield.
- On and off switch for front wheel and cutter spindle drive (VR 60 B and VR 45 A) on the guide beam.
- Smooth running, enclosed and maintenance-free pull cable to operate the drive belt couplings.
- Cutter spindle drive via dual drive belt.
- Large-sized, maintenance-free ball bearings on the cutter spindle to absorb shocks and provide a long service life.
- Optionally available with sledge or slit cutter spindle, add-ons are possible at any time due to easy and complete interchangeability.

Hand Roller HR 60



Specifications	HR 60
Smooth roller diameter	46 cm
Working width	60 cm
Curb weight	57 kg
maximum weight up to	155 kg
Lattice roller diameter	35 cm
Working width	60 cm
Weight	22 kg
Seed dibbler diameter	18 cm
Working width	60 cm
Weight	35 kg

The new SEMBDNER HR 60 hand roller is available in a heavy-duty steel construction.

Small Engine Roller KM 1 – KM 2



Specifications	KM 1	KM 2
Roller width	80 cm	80 cm
Roller diameter	50 cm	50 cm
Length/width/height	1520/930/1050 mm	1520/930/1050 mm
HONDA engine GX 160	4 kW / 5.5 HP	4 kW / 5.5 HP
4-stroke gas engine with automatic oil guard shut-off		
Speed (more if desired)	up to 4.5 km/h	up to 4.5 km/h
Separated roller (differential drive) with maintenance-free differential drive for easy steering and turning	○	●
Approx. area capacity per hour	3,500 m ²	3,500 m ²
Operating weight – without water	275 kg	315 kg
Operating weight – with water	395 kg	415 kg
Linear roller pressure – without water	3.5 kg/cm	4.0 kg/cm
Linear roller pressure – with water	5.0 kg/cm	5.2 kg/cm

The SEMBDNER small engine rollers are ideally suited for all rolling operations to maintain and service tennis courts and sports facilities, such as tracks, hard surfaces and lawn areas.

SEMBDNER
Maschinenbau Kleinmotorwalzen
Sämaschinen

Sembdner Str. 1 · 82110 Germering
Germany
Telephone: +49 (89) 84 23 77
Fax: +49 (89) 8 40 24 52
www.sembdner.com
E-Mail: info@sembdner.com

Dealer stamp

SEMBDNER
Maschinenbau Kleinmotorwalzen
Sämaschinen

Lawn Maintenance Program



Since 1914