

## Scarifier

### VR 60 B – VR 45 A

*powerful,  
 robust and practical  
 for professional  
 long-term use*



Specifications	VR 60 B	VR 45 A
Front wheel drive	x	x
Reduction gear 55 :1 (for front wheel drive)	x	x
Working width	60 cm	45 cm
Ground working depth up to	up to 2,5 cm	up to 2,5 cm
Weight	110 kg	90 kg
HONDA engines	6.6 kW/9 hp	4 kW/5.5 hp
4-stroke petrol engine with automatic oil guard shut-off		
Approx. area capacity per hour	2,000 m <sup>2</sup>	1,500 m <sup>2</sup>
l/w/h approx. (with guide beam)	1,360/800/990 mm	1,360/650/990 mm
Steel panel housing	4 mm	4 mm
Inflatable tires	260 x 85	260 x 85

## Features

- Front wheel drive for an even and optimal result and easy, comfortable operation, on level or hilly ground.
- Heavy-duty steel construction for continuous professional use.
- Large and wide inflatable tires as well as rear wheels with individual suspension for turning in the tightest space.
- Security mechanism for simultaneous shut-off of wheel drive and cutter spindle.
- Practical safety covers and ejection safeguards with movable rubber shield.
- On and off switch for front wheel and cutter spindle drive on the handle bar.
- Smooth running, encapsuled and maintenance-free cable to operate the drive belt couplings.
- Cutter spindle drive via dual drive belt.
- Large-sized, maintenance-free ball bearings on the cutter spindle to absorb shocks and provide a long life.
- Optionally available with sledge or slit cutter spindle, add-ons are possible at any time due to easy and complete interchangeability.
- powerful 9 hp or 5.5 hp Honda engine
- . high area capacity thanks to 60 cm or 45 cm working width
- scrapers on the rear wheels
- . height-adjustable guide spar
- blade shaft drive via double V-belt
- fast adjustment of precise working depths directly from the operator position
- sturdy toolbox with tools



View of the drive technologies

## Different equipment versions

The following blade shafts are available, equipped with flail blades or slitting blades made from hardened spring steel.



The **flail blade shaft** on the VR 60 B is equipped with 66 replaceable blades and on the VR 45 A with 48.



The **slitting blade shaft** on the VR 60 B is equipped with 24 individually replaceable blades and on the VR 45 A with 18.

### Manufacturer / Sales:

Sembdner Maschinenbau GmbH  
Liebigstr. 16  
D – 82256 Fürstenfeldbruck  
Tel.: +49 8141 818 51-0  
Fax: + 49 8141 818 51-14  
Mail: [info@sembdner.com](mailto:info@sembdner.com)  
[www.sembdner.com](http://www.sembdner.com)